

TECHNICKÁ SPECIFIKACE

název série	šířka (L) mm	výška (H) mm	rozteč	hloubka		výkon při tep. spádu			váha kg	objem dm3	povrch m2	koeficient n	doporučený výkon el.tyče W
			připojení	od zdi vč.	od zdi k	55/45	75/65	90/70					
			středové (h) mm	radiátoru (G) mm	přívodu (g) mm	20°C W	20°C W	20°C W					
NAMELESS	400	930	50	94-104	68-78	156	296	372	10,4	3,0	0,75	1,2558	300
		1186				194	369	463	14,0	3,8	1,00	1,2561	400
		1610				245	466	585	17,0	4,9	1,25	1,2564	400
		1824				271	516	649	20,0	6,0	1,50	1,2573	600
	500	930	50	94-104	68-78	186	355	447	12,0	3,4	0,93	1,2652	400
		1186				232	441	555	15,0	4,4	1,25	1,2600	400
		1610				294	558	701	19,0	5,6	1,56	1,2531	600
		1824				325	619	778	23,7	6,9	1,88	1,2587	600
	600	930	50	94-104	68-78	214	411	519	13,8	3,9	1,11	1,2747	400
		1186				269	512	645	17,8	5,0	1,60	1,2640	600
		1610				342	647	813	22,8	6,4	2,34	1,2499	600
		1824				377	718	903	27,3	7,8	2,49	1,2601	600

