

LAUFEN INSTALLATION SYSTEM

TW1 Concealed frame with cistern for wallhung WC 89466.3



TECHNICAL DATA

Order no.	89466.3	Tank	Thickness 110 mm, material PP
Certified to	EN 14055	Installation depth	125 mm
matching for	All LAUFEN wallhung toilets	Weight	8,5 kg
Specifications	For mounting on brick wall (not suitable for drywall or concrete installation), wall mounting, with frontal actuator, with water condensation insulation. Dual-Flush 6/3-l (4/2-l-flush). Flush valve with silicon seal. Fill valve with anti-siphon system.	Mounting acc. incl.	Fastening set for the wall, WC connection set, tiling set, protection caps (for WC connection pipes) and protection tubes for M12 threaded rods, angle valve 1/2".
Other specifications	Galvanized supporting "U-shaped" with fixing points adjustable to the wall. Supporting frame made of steel profiles. Capable to resist 400 kg	Accessories excl.	Actuator plates dual flush, order no. 89566.1, 89566.2 (stainless steel) Electronic actuator plate dual flush, order no. 89566.3, 89566.4
Water inlet	top or rear R 1/2", brass	Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of WC pre-set to 400 mm, adjustable between 390-450 mm. System installation is also possible between modular walls (plasterboard).
Outlet	DN 100 ABS	Colours	Surface powder coated grey
Flow pressure range	0.5-10 bar		
Water temperature	max. 25°C		

TECHNICAL DRAWINGS / S 1 : 20

